

7545 Irvine Center Drive Irvine, California 92618 Phone: 949.623.8328 Fax: 949.861.7475 www.moxieinductors.com

MoxiE Inductor Corporation Audio Jack Quick Reference Guide























































AUDIO JACK QUICK REFERENCE GUIDE

	MOX-AJ35-3TA THREADED
PRODUCT TYPE:	3.5mm STEREO JACK
NUMBER OF POLES:	3
NUMBER OF CONTACTS	3
MOUNTING TYPE:	DIP
CONTACT RESISTANCE:	30mΩ MAXIMUM
INSULATION RESISTANCE:	100MΩ MIN @ 500Vdc
WITHSTAND VOLTAGE:	500V AC FOR 1 MIN.
FLAMMABILITY:	UL94V-0 RATED
LIFE CYCLE:	5000 CYCLES
MOXIE CUSTOM DESIGNS:	AVALABLE

	MOX-AJ35-5NTA NON-THREADED
PRODUCT TYPE:	3.5mm STEREO JACK
NUMBER OF POLES:	3
NUMBER OF CONTACTS	5
MOUNTING TYPE:	DIP
CONTACT RESISTANCE:	30mΩ MAXIMUM
INSULATION RESISTANCE:	50MΩ MIN @ 500Vdc
WITHSTAND VOLTAGE:	500V AC FOR 1 MIN.
FLAMMABILITY:	UL94V-0 RATED
LIFE CYCLE:	5000 CYCLES
MOXIE CUSTOM DESIGNS:	AVALABLE

0	MOX-AJ35-8NTA NON-THREADED
PRODUCT TYPE:	3.5mm STEREO JACK
NUMBER OF POLES:	3
NUMBER OF CONTACTS	8
MOUNTING TYPE:	DIP
CONTACT RESISTANCE:	30mΩ MAXIMUM
INSULATION RESISTANCE:	100MΩ MIN @ 500Vdc
WITHSTAND VOLTAGE:	500V AC FOR 1 MIN.
FLAMMABILITY:	UL94V-0 RATED
LIFE CYCLE:	5000 CYCLES
MOXIE CUSTOM DESIGNS:	AVALABLE

0	MOX-AJ35-5NTB NON-THREADED
PRODUCT TYPE:	3.5mm STEREO JACK
NUMBER OF POLES:	3
NUMBER OF CONTACTS	5
MOUNTING TYPE:	DIP
CONTACT RESISTANCE:	30mΩ MAXIMUM
INSULATION RESISTANCE:	100MΩ MIN @ 500Vdc
WITHSTAND VOLTAGE:	500V AC FOR 1 MIN.
FLAMMABILITY:	UL94V-0 RATED
LIFE CYCLE:	5000 CYCLES
MOXIE CUSTOM DESIGNS:	AVALABLE

0	MOX-AJ35-5NTC NON-THREADED
PRODUCT TYPE:	3.5mm STEREO JACK
NUMBER OF POLES:	3
NUMBER OF CONTACTS	5
MOUNTING TYPE:	DIP
CONTACT RESISTANCE:	30mΩ MAXIMUM
INSULATION RESISTANCE:	100MΩ MIN @ 500Vdc
WITHSTAND VOLTAGE:	500V AC FOR 1 MIN.
FLAMMABILITY:	UL94V-0 RATED
LIFE CYCLE:	5000 CYCLES
MOXIE CUSTOM DESIGNS:	AVALABLE

	MOX-AJ35-11NTA NON-THREADED
PRODUCT TYPE:	3.5mm STEREO JACK
NUMBER OF POLES:	3
NUMBER OF CONTACTS	11
MOUNTING TYPE:	DIP
CONTACT RESISTANCE:	30mΩ MAXIMUM
INSULATION RESISTANCE:	100MΩ MIN @ 500Vdc
WITHSTAND VOLTAGE:	500V AC FOR 1 MIN.
FLAMMABILITY:	UL94V-0 RATED
LIFE CYCLE:	5000 CYCLES
MOXIE CUSTOM DESIGNS:	AVALABLE

MOX-AJ35-5NTD NON-THREADED
3.5mm STEREO JACK
3
5
DIP
30mΩ MAXIMUM
100MΩ MIN @ 500Vdc
500V AC FOR 1 MIN.
UL94V-0 RATED
5000 CYCLES
AVALABLE

्र _{विवि} वि	MOX-AJ35-5NTE NON-THREADED
PRODUCT TYPE:	3.5mm STEREO JACK
NUMBER OF POLES:	3
NUMBER OF CONTACTS	5
MOUNTING TYPE:	DIP
CONTACT RESISTANCE:	30mΩ MAXIMUM
INSULATION RESISTANCE:	100MΩ MIN @ 500Vdc
WITHSTAND VOLTAGE:	500V AC FOR 1 MIN.
FLAMMABILITY:	UL94V-0 RATED
LIFE CYCLE:	5000 CYCLES
MOXIE CUSTOM DESIGNS:	AVALABLE

MOX-AJ35-5TA THREADED
3.5mm STEREO JACK
3
3
DIP
30mΩ MAXIMUM
100MΩ MIN @ 500Vdc
500V AC FOR 1 MIN.
UL94V-0 RATED
5000 CYCLES
AVALABLE

	MOX-AJ35-5NTF NON-THREADED
PRODUCT TYPE:	3.5mm STEREO JACK
NUMBER OF POLES:	3
NUMBER OF CONTACTS	5
MOUNTING TYPE:	DIP
CONTACT RESISTANCE:	30mΩ MAXIMUM
INSULATION RESISTANCE:	100MΩ MIN @ 500Vdc
WITHSTAND VOLTAGE:	500V AC FOR 1 MIN.
FLAMMABILITY:	UL94V-0 RATED
LIFE CYCLE:	5000 CYCLES
MOXIE CUSTOM DESIGNS:	AVALABLE

	MOX-AJ35-11NTB NON-THREADED
PRODUCT TYPE:	3.5mm STEREO JACK
NUMBER OF POLES:	3
NUMBER OF CONTACTS	11
MOUNTING TYPE:	DIP
CONTACT RESISTANCE:	30mΩ MAXIMUM
INSULATION RESISTANCE:	100MΩ MIN @ 500Vdc
WITHSTAND VOLTAGE:	500V AC FOR 1 MIN.
FLAMMABILITY:	UL94V-0 RATED
LIFE CYCLE:	5000 CYCLES
MOXIE CUSTOM DESIGNS:	AVALABLE

	MOX-AJ35-5TB THREADED
PRODUCT TYPE:	3.5mm STEREO JACK
NUMBER OF POLES:	3
NUMBER OF CONTACTS	3
MOUNTING TYPE:	DIP
CONTACT RESISTANCE:	30mΩ MAXIMUM
INSULATION RESISTANCE:	100MΩ MIN @ 500Vdc
WITHSTAND VOLTAGE:	500V AC FOR 1 MIN.
FLAMMABILITY:	UL94V-0 RATED
LIFE CYCLE:	5000 CYCLES
MOXIE CUSTOM DESIGNS:	AVALABLE